

# RUST BREAKER® PENETRANT



## LU™ 103



Light Pressure Lubricant




NSF® Registered; H2 Rated (Lubricants with no contact) (Registration # 127526)



Dielectric strength value: 47,400 Volts



Minimum - Maximum operational temperature range: Low -20 °F (-29 °C) • High 550 °F (288 °C)



Flash Point: 205 °F (96 °C)



HMS Hazard Rating:  
Health (2) • Flammability (0) • Reactivity (0)

- Non-flammable propellant
- Will not harm painted surfaces
- Loosens rust and frozen parts
- Fast penetration




PRESERVE. PROTECT. PREVENT.™

Sprayon® LU™ 103 Rust Breaker® Penetrant is a fast-acting product that quickly loosens rust while penetrating grease and dirt. A transparent, non staining oil, its light film displaces moisture and acts as a corrosion preventative. Jet stream sprays up to two feet for safe, accurate application. It is a one coat rust and corrosion preventive compound. Pleasant vanilla scent.

## LUBRICANTS

### USES

- Release rusted or frozen lugs and bolts
- Repair work
- General overhaul
- For use on phosphated or non-phosphated machined parts
- Automotive parts
- Crank shafts
- Other metal components



LU103

© 2010 Sprayon® Products Made in U.S.A.

### APPLICATION

Maximum performance is achieved when the metal surfaces to be protected are clean, dry and free of rust, oil and mill scale. Product should be sprayed in a well ventilated area. Sprays best at room temperature (70°F.). Shake well before using. Spray at a distance of 10" to 12" from surface.

### PERFORMANCE

**DIELECTRIC STRENGTH:** 47,400 volts

**PLASTIC SAFE:** Yes

**TEMPERATURE RANGE:**

**LOW:** -20°F

**HIGH:** 550°F

**LOAD CAPACITY:** Low

**SALT SPRAY CORROSION**

(ASTM B-117): will withstand over 120 hrs.

**HUMIDITY CABINET TEST**

(ASTM D-1748): 2,000 hours minimum

- NSF Registration Number: 115050, H2 Rated
- Penetrant
- Water-Displacer
- Rust Inhibitor
- Non-flammable propellant
- Equipped with SPRAY ANYWAY™ valve and extension tube
- Jet stream spray for safe accurate application
- Active water displacing, creep, and penetrating properties

### PACKAGING

**Stock #:** S00103

**UPC Code:** 0-75577-90103-6

**Fill Wt.:** 10 oz.

**Per Case:** 12

**Carton Dimensions:**

L 10-7/8" x W 8-3/16" x H 8"

### PROPERTIES

**APPEARANCE:** Light amber

**ODOR:** Vanilla

**PROPELLANT:** CO2

**WT./GAL.:** 6.68

**SPECIFIC GRAVITY:** 0.80

**PAINTABLE:** No

**H.A.P.S. (Hazardous Air Pollutants):** No

**SARA 313 Chemicals:** No

**PROP 65:** No

**% VOC AEROSOL:** 85%

**V.O.C. COMPLIANT CALIFORNIA:** Yes

**V.O.C. COMPLIANT OTC STATES:** Yes

**FLAMMABLE:** Yes

**FLASH POINT:** >200°F

**HAZARD RATING:**

S00103 - 2,4,0;

**SHELF LIFE:** 3 years from date of manufacture

### SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

### RESOURCES

**MSDS/EDS/PRODUCT DATA SHEETS:**

sprayon.com

**CUSTOMER SERVICE:**

1-800-777-2966

**TECHNICAL INFORMATION:**

1-800-251-2486



Distributed by:

**Lawson Products, Inc.**

To order these and other products, contact us:  
866-529-7664 lawsonproducts.com

PRESERVE. PROTECT. PREVENT.



**Sprayon® Products**

101 Prospect Ave. NW  
Cleveland, OH 44115  
Sprayon.com  
1-800-777-2966

310-PDS-LU103