



Overview

Persist is an all-purpose, non-melt grease that is formulated with extreme pressure and anti-wear additives for staying power and pound-out resistance. It protects surfaces long after ordinary greases are squeezed out. Persist has a high temperature rating of +500°F (260°C), and reduces lubrication frequency and grease costs.

Features/Benefits

- Contains rust, corrosion and oxidation inhibitors
- Extreme pressure and anti-wear additives give Persist a 65 Timkin load rating
- Operating range of -40°F to +500°F (-40°C to +260°C) for continuous protection
- Acceptable for use in federally inspected meat and poultry plants
- Resistant to water washout and shock impact

Applications

- Rust, corrosion and oxidation inhibitors to help resist water, steam, salt spray and most acids
- Extreme-pressure and anti-wear additives
- Tackifiers and adhesive/cohesive additives that provide staying power, resist shock impact and won't pound out – grease stays where it is applied

Method of Application

Cartridge

Identification

Extreme Pressure Grease

Size

14 Oz.

Directions for Use

Apply grease generously to equipment in need of lubrication. Reapply as needed. Extreme pressure greases must be reapplied frequently. Likely monthly.

Technical Specifications

- TEMPERATURE RANGE: -5F to 500F (40F to 450F Optimal)
- THICKENER: Bentonite
- COLOR: Red
- DROPPING POINT (ASTM D-566): >550F
- FLASH POINT (ASTM D-92): >400F
- TIMKEN OK LOAD MIN: 65

