



PROFESSIONAL



PROFESSIONAL

First Class Friction Reduction

Z-Works PTFE Lubricant and Z-Works Aerosol PTFE Lubricant

Take lubrication to a whole new level with these premium, long-lasting lubricants. The PTFE in both our bulk and aerosol formulations reduces friction to previously impossible levels, leaving a lasting friction-reducing film. These top-quality lubricants also quickly penetrate to loosen parts frozen due to wear, corrosion and grime build-up.

Benefits:

- Rapidly penetrates and lubricates
- Leaves a non-stick coating on moving parts
- Corrosion resistance properties
- Available in economical bulk and convenient aerosol formulations

Applications:

Z-Works PTFE lubricant should be applied to equipment before working to lubricate and protect the equipment:

- Industrial machinery
- Motor shafts
- Firearms
- Saws
- Drills
- Office equipment
- Hinges

Directions for Use:

BULK: Shake solution before filling sprayer.

AEROSOL: Spray on tight or rusty parts.



Base Codes: R070, R074

Companion Products:

Base Code

Z-Works High Pressure LubricantR071

Z-Works Soy Penetrating LubricantR073



1-877-7ZEPRO | www.zepprofessional.com

Lubricants & Penetrants


Distributed by: Lawson Products, Inc.

To order these and other products, contact us: 866-529-7664 lawsonproducts.com



Specifications:

Physical Form	Aerosol
Propellant Type	CO ₂
Can Size	24 fl oz
Net Weight	1 lb. 2 oz. avdp (522g)
Storage Temperature	32°F to 120°F (0°C to 49°C)
Flammability	Flammable CSMA flame extension
Shelf Life	1 year minimum
Lubricant Type	Fluoropolymers
D.O.T. Shipping	ORM-D



Specifications:

Physical Form	Thin, solvent-based liquid
Color	Clear, amber
Density-Specific Gravity	6.92 lbs./gal. - 0.83
Flash Point (TCC)	110°F (43.3°C)
Shelf Life	1 year minimum
D.O.T. Shipping	none

Packaging Information:

SKU	Package Quantity	Weight (lbs)	Length (")	Height (")	Width (")
R07001	12-24oz cans/case	17	12.70	10.00	9.60
R07424	4-1 gal/case	35	13.00	13.00	12.50

Safety:

Please make sure you have read and understand the product label and MSDS before using this product. MSDSs are available at www.zepprofessional.com. Avoid contact with eyes, skin and clothing. Avoid breathing vapors, spray or mists. Use only with adequate ventilation. Watch for accumulation in low confined areas. Store and use away from heat, sparks, open flame or any other ignition source. Do not ingest. Wash thoroughly after handling. Wash contaminated clothing before reusing. Observe label precautions.



PROFESSIONAL

Zep Professional, a unit of Zep Inc.
 ISO 9001 & ISO 14001 Certified
 ZPSS-R070/R074 • 1208a

1-877-7ZEPPRO | www.zepprofessional.com