



# CRIMPER STARTER ASSORTMENTS

## Crimper Starter Assortments



Lawson's Crimper Starter Assortments are turnkey solutions for customers using 2-wire braided hydraulic hose. Each kit includes a crimper, pump, applicable collets and and/or spacer rings, hydraulic hose and fittings, and cabinetry. Create OEM-quality hydraulic hose assemblies with one of our Crimper Starter Assortment options.

### Starter Assortments include:

- Crimper
- Air/Hydraulic or Electric Pump
- All necessary tooling to crimp -4, -6, and -8 size hose and fittings within each Crimper Starter Assortment
- One 50-foot roll each of -4, -6, and -8 2-wire braided hose
- 26 unique SKUs covering NPT, JIC and FFOR connection styles
- A40 Bin and A1C11 3-hole compartment



ET1000



KH-60-P  
(Portable)



KH-60  
(Bench Mount)

Description	Crimper	Power Source	Hose	Fitting	Fitting Item and Piece Count	Item No.	Pkg. Qty.
ET1000 Crimper Starter Assortment	ET1000	Air/Hydraulic	H280	Z Series	26 Items, 129 Pieces	AP1000Z280	1
	ET1000	Electric 110V	H280	Z Series	26 Items, 129 Pieces	EP1000Z280	1
	ET1000	Air/Hydraulic	EC215	Z Series	26 Items, 129 Pieces	AP1000Z215	1
	ET1000	Electric 110V	EC215	Z Series	26 Items, 129 Pieces	EP1000Z215	1
KH-60-P Crimper Starter Assortment	KH-60-P (Portable)	Air/Hydraulic	R16S	KH Series	26 Items, 115 Pieces	APKH60KR16	1
KH-60 Crimper Starter Assortment	KH-60 (Bench Mount)	Electric 120V	R16S	KH Series	26 Items, 115 Pieces	EPKH60KR16	1

Fitting End Style	Gender	Fitting Angle	Fitting End Type	Fitting Dimension A (Hose)	Fitting Dimension B (Working End)
Pipe NPTF	Male	Straight	Rigid	1/4 (-4)	1/4-18 (-4)
		Straight	Rigid	3/8 (-6)	3/8-18 (-6)
		Straight	Rigid	1/2 (-8)	1/2-14 (-8)
		Straight	Swivel	1/4 (-4)	7/16-20 (-4)
		Straight	Swivel	1/4 (-4)	9/16-18 (-6)
		Straight	Swivel	3/8 (-6)	9/16-18 (-6)
		Straight	Swivel	3/8 (-6)	3/4-16 (-8)
JIC 37° Flare	Female	Straight	Swivel	1/2 (-8)	3/4-16 (-8)
		Straight	Swivel	1/2 (-8)	7/8-14 (-10)
		45°	Swivel	1/4 (-4)	7/16-20 (-4)
		45°	Swivel	3/8 (-6)	9/16-18 (-6)
		45°	Swivel	1/2 (-8)	3/4-16 (-8)
		90°	Swivel	1/4 (-4)	7/16-20 (-4)
		90°	Swivel	1/4 (-4)	9/16-18 (-6)
		90°	Swivel	3/8 (-6)	9/16-18 (-6)
		90°	Swivel	1/2 (-8)	3/4-16 (-8)
		90°	Swivel	1/2 (-8)	7/8-14 (-10)
Flat Face O-Ring Seal	Female	Straight	Rigid	1/4 (-4)	7/16-20 (-4)
		Straight	Rigid	3/8 (-6)	9/16-18 (-6)
		Straight	Rigid	3/8 (-6)	3/4-16 (-8)
		Straight	Rigid	1/2 (-8)	3/4-16 (-8)
		Straight	Swivel	1/4 (-4)	9/16-18 (-4)
		Straight	Swivel	3/8 (-6)	11/16-16 (-6)
		Straight	Swivel	1/2 (-8)	13/16-16 (-8)
45°	Swivel	3/8 (-6)	11/16-16 (-6)		
90°	Swivel	1/2 (-8)	13/16-16 (-8)		

