




## Reamers

- Regency® Reamers will enter holes half their nominal diameter
- Special gold finish that minimizes friction
- Three large flats for solid chucking
- Right-hand cut with left-hand flute to minimize pushback or grabbing

NOTE: Always use slow turning drill motors of 4.5 amps or higher.



Dia. (Inches)	Material Thickness	Pilot Drill Dia.	Overall Length (Inches)	Recommended Drill Item No.	Item No.	Pkg. Qty.
3/8	1	3/16	4	<b>84729</b>	<b>86861</b>	1
1/2	1-1/4	1/4	4-1/2	<b>84733</b>	<b>86862</b>	1
5/8	1-1/2	5/16	5	<b>84737</b>	<b>86890</b>	1
3/4	1-3/4	3/8	5-1/2	<b>84741</b>	<b>86891</b>	1
7/8	2	7/16	6-1/8	<b>84745</b>	<b>97624</b>	1
1	2-1/4	1/2	6-3/4	<b>84749</b>	<b>97625</b>	1

## Drill and Reamer Sets

Dia.	Item No.	Pkg. Qty.
3/8 to 3/4 by 8ths	<b>91894</b>	1
	<b>1561751*</b>	1

\*Comes supplied in a high-impact storage index



## Kit Components

Description	Item No.	Qty.
Regency® Reamer, 3/8"	<b>86861</b>	1
Regency® Reamer, 1/2"	<b>86862</b>	1
Regency® Reamer, 5/8"	<b>86890</b>	1
Regency® Reamer, 3/4"	<b>86891</b>	1
Regency® Jobber Length Drill Bit, 3/16"	<b>84729</b>	1
Regency® Jobber Length Drill Bit, 1/4"	<b>84733</b>	1
Regency® Jobber Length Drill Bit, 5/16"	<b>84737</b>	1
Regency® Jobber Length Drill Bit, 3/8"	<b>84741</b>	1

CAUTION: Any cutting tool may break or shatter under improper use. Government regulations require use of safety glasses and other appropriate safety equipment at all times in the vicinity of use.