



FLEXAIR Hose Assembly



FLEXAIR hybrid polymer hose assemblies combine the best characteristics of PVC and rubber. Ultra-flexible and tough, they provide an optimized flow rate for pneumatic tools. The protective rubber guard around the ferrules eliminates scratches and reduces the strain on the hose.

- Temperature range: -40°F to +140°F (-40°C to +60°C)
- Rated at 300 PSI working pressure
- Reinforcement: One fiber braid
- Cover: Hybrid polymer (blue)
- Inner tube: Hybrid polymer
- Ultra-flexible
- Lightweight and easy to handle
- Non-scratch material
- Kink-resistant

I.D. (Inches)	Working Pressure (PSI)	Length (Ft.)	End Fittings	Item No.	Pkg. Qty.
3/8	300	25	1/4" NPT	1585089	1
	300	35	1/4" NPT	1585090	1
	300	50	1/4" NPT	1585091	1



FLEXAIR Hose Assembly with Push-Button Safety Coupler

Description	I.D. (Inches)	Working Pressure (PSI)	Length (Ft.)	End Fittings	Item No.	Pkg. Qty.
Air Hose Assembly with Industrial Interchange Push-Button Safety Coupler	3/8	300	50	1/4" NPT	1585088	1
Air Hose Assembly with Tru-Flate Push-Button Safety Coupler	3/8	300	50	1/4" NPT	1585092	1

