

Issue date 05-Jun-2018

Revision date 07-Nov-2022

Revision Number 2

1. IDENTIFICATION

Product identification

Product identifier	Lawson Chevrolet Orange High Solids Engine Paint
Other means of identification	1509167
Recommended use	Paint
Restrictions on use	Not applicable

Supplier

Corporate Headquarters:
Lawson Products, Inc.
8770 W. Bryn Mawr Ave., Suite 900
Chicago, IL 60631
(866) 837-9908

Canadian Distribution Center:
Lawson Canada
7315 Rapistan Court
Mississauga, ON L5N 5Z4
(800) 323-5922

24 Hour Emergency Phone Number (888) 426-4851 (Prosar)

Website www.lawsonproducts.com

2. HAZARD(S) IDENTIFICATION

Hazard Classification This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), WHMIS 2015 and GHS Regulations.

Serious eye damage/eye irritation	Category 2A
Specific target organ toxicity (single exposure)	Category 3
Specific target organ toxicity (repeated exposure)	Category 2
Flammable aerosols	Category 1
Gases under pressure	Compressed gas

Symbol

Signal word
DANGER
Hazard statements

H222 - Extremely flammable aerosol
H280 - Contains gas under pressure; may explode if heated
H319 - Causes serious eye irritation
H336 - May cause drowsiness or dizziness

H373 - May cause damage to organs through prolonged or repeated exposure

Precautionary statements

General
P101 - If medical advice is needed, have product container or label at hand
P103 - Read label before use.
P102 - Keep out of reach of children

Prevention
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 - Do not spray on an open flame or other ignition source
P251 - Pressurized container: Do not pierce or burn, even after use
P264 - Wash hands thoroughly after handling
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear protective gloves/protective clothing and eye/face protection
P260 - Do not breathe dust/fume/gas/mist/vapors/spray

Response

General
P312 - Call a POISON CENTER or doctor if you feel unwell

Eyes
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P337 + P313 - If eye irritation persists: Get medical advice/attention

Inhalation
P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

Storage
P405 - Store locked up
P412 - Do not expose to temperatures exceeding 50 °C/122 °F
P410 - Protect from sunlight
P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

Disposal
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Hazard(s) Not Otherwise Classified (HNOC)
None known.

Physical Hazards Not Otherwise Classified (PHNOC)
None known.

Unknown acute toxicity
None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Composition This product is a mixture of the substances listed below with nonhazardous additions.

Chemical name	CAS-No	Weight %
Acetone	67-64-1	21.7
Propane	74-98-6	17.69
n-Butyl acetate	123-86-4	11.43
N-Butane	106-97-8	10.39
Isobutyl acetate	110-19-0	9.34
Toluene	108-88-3	3.09
Ethylene glycol monopropyl ether	2807-30-9	2.77
Methylisobutyl ketone	108-10-1	2.46
Titanium dioxide	13463-67-7	<1

Methanol	67-56-1	<1
Ethyl benzene	100-41-4	<1

4. FIRST-AID MEASURES

Necessary first-aid measures

- Inhalation** Supply fresh air. Consult doctor in case of complaint.
- Ingestion** Rinse mouth with water. Do NOT induce vomiting.
- Skin contact** Remove contaminated clothing. Wash exposed area with soap and water.
- Eye contact** Rinse opened eye for several minutes under running water. If symptoms persist, call a physician.

Most important symptoms (acute) Dizziness.

Most important symptoms (over-exposure) No further relevant information available.

Indication of any immediate medical attention and special treatment needed No further relevant information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media Carbon dioxide (CO2). Extinguishing powder. Water spray. Fight larger fires with water spray.

Unsuitable extinguishing media Not available.

Specific hazards Can form explosive gas-air mixtures.

Special protective equipment for fire-fighters A respiratory protective device may be necessary.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Use respiratory protective device against the effects of fumes/dust/aerosol.

Methods and materials for containment and cleaning up Absorb liquid components with liquid-binding material.

7. HANDLING AND STORAGE

Precautions for safe handling Use only in a well ventilated area.

Conditions for safe storage, including any incompatibilities Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions. Store locked up.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Chemical name	OSHA PEL (TWA)	California - PELs	ACGIH OEL (TWA)	NIOSH - TWA
Acetone	1000 ppm TWA 2400 mg/m ³ TWA	500 ppm PEL; 1200 mg/m ³ PEL	250 ppm TWA	250 ppm TWA 590 mg/m ³ TWA
Propane	1000 ppm TWA 1800 mg/m ³ TWA	1000 ppm PEL; 1800 mg/m ³ PEL		1000 ppm TWA 1800 mg/m ³ TWA 1000 ppm TWA 1800 mg/m ³ TWA
n-Butyl acetate	150 ppm TWA 710 mg/m ³ TWA	150 ppm PEL; 710 mg/m ³ PEL	50 ppm TWA	150 ppm TWA 710 mg/m ³ TWA
N-Butane	-	800 ppm PEL; 1900 mg/m ³ PEL		800 ppm TWA 1900 mg/m ³ TWA 1000 ppm TWA 1800 mg/m ³ TWA
Isobutyl acetate	150 ppm TWA 700 mg/m ³ TWA	150 ppm PEL; 700 mg/m ³ PEL	50 ppm TWA	150 ppm TWA 700 mg/m ³ TWA
Toluene	200 ppm TWA	10 ppm PEL; 37 mg/m ³ PEL	20 ppm TWA	100 ppm TWA 375 mg/m ³ TWA
Ethylene glycol monopropyl ether	-			
Methylisobutyl ketone	100 ppm TWA 410 mg/m ³ TWA	50 ppm PEL; 205 mg/m ³ PEL	20 ppm TWA	50 ppm TWA 205 mg/m ³ TWA
Titanium dioxide	15 mg/m ³ TWA	5 mg/m ³ PEL (respirable fraction, listed under Particulates not otherwise regulated); 10 mg/m ³ PEL (total dust, listed under Particulates not otherwise regulated)	0.2 mg/m ³ TWA 2.5 mg/m ³ TWA	2.4 mg/m ³ TWA 0.3 mg/m ³ TWA
Methanol	200 ppm TWA 260 mg/m ³ TWA	200 ppm PEL; 260 mg/m ³ PEL	200 ppm TWA Skin	200 ppm TWA 260 mg/m ³ TWA
Ethyl benzene	TWA: 100 ppm TWA: 435 mg/m ³	5 ppm PEL; 22 mg/m ³ PEL	20 ppm TWA	100 ppm TWA 435 mg/m ³ TWA

Appropriate engineering controls Not available.

Individual protection measures, such as personal protective equipment

- Eye protection** Tightly fitting safety goggles.
- Skin and body protection** Nitrile gloves. Protective gloves. The glove material must be impermeable and resistant to the substance.
- Respiratory protection** A respirator is generally not necessary when using this product outdoors or in a large open areas. In cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn. If you suspect overexposure conditions exist, please consult an authority on chemical hygiene.
- Hygiene measures** Immediately remove all soiled and contaminated clothing. Wash hands after use. Avoid contact with skin and eyes. Do not eat or drink while working.

Canadian Province Occupational Exposure Limits

Chemical name	AB	BC	MB	NB	NL	NS	ON	PE	QC	SK
Acetone	500 ppm TWA 1200 mg/m ³ TWA	250 ppm TWA	250 ppm TWA	500 ppm TWA 1188 mg/m ³ TWA	250 ppm TWA	250 ppm TWA	250 ppm TWA	250 ppm TWA	500 ppm TWA 1190 mg/m ³ TWA	500 ppm TWA

Chemical name	AB	BC	MB	NB	NL	NS	ON	PE	QC	SK
Propane	1000 ppm TWA 1640 mg/m ³ TWA	1000 ppm TWA	-	1000 ppm TWA 1640 mg/m ³ TWA	-	-	-	-	1000 ppm TWAEV 1800 mg/m ³ TWAEV 1000 ppm TWAEV 1640 mg/m ³ TWAEV	1000 ppm TWA 1000 ppm TWA 1000 ppm TWA
n-Butyl acetate	150 ppm TWA 713 mg/m ³ TWA	50 ppm TWA	50 ppm TWA	150 ppm TWA 713 mg/m ³ TWA	50 ppm TWA 50 ppm TWA	50 ppm TWA	50 ppm TWA	50 ppm TWA 50 ppm TWA	50 ppm TWAEV	150 ppm TWA
N-Butane	1000 ppm TWA 1640 mg/m ³ TWA	1000 ppm TWA	-	800 ppm TWA 1900 mg/m ³ TWA 1000 ppm TWA 1640 mg/m ³ TWA	-	-	-	-	800 ppm TWAEV 1900 mg/m ³ TWAEV 1000 ppm TWAEV 1640 mg/m ³ TWAEV	1000 ppm TWA 1000 ppm TWA 1000 ppm TWA 1000 ppm TWA
Isobutyl acetate	150 ppm TWA 713 mg/m ³ TWA	50 ppm TWA	50 ppm TWA	150 ppm TWA 713 mg/m ³ TWA	50 ppm TWA 50 ppm TWA	50 ppm TWA	50 ppm TWA	50 ppm TWA 50 ppm TWA	50 ppm TWAEV	150 ppm TWA
Toluene	50 ppm TWA 188 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA 188 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	50 ppm TWAEV 188 mg/m ³ TWAEV	50 ppm TWA
Ethylene glycol monopropyl ether	-	-	-	-	-	-	25 ppm TWA 110 mg/m ³ TWA	-	-	-
Methylisobutyl ketone	50 ppm TWA 205 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	50 ppm TWA 205 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWAEV	50 ppm TWA
Titanium dioxide	10 mg/m ³ TWA	10 mg/m ³ TWA 3 mg/m ³ TWA	0.2 mg/m ³ TWA 2.5 mg/m ³ TWA	10 mg/m ³ TWA	0.2 mg/m ³ TWA 2.5 mg/m ³ TWA	0.2 mg/m ³ TWA 2.5 mg/m ³ TWA	10 mg/m ³ TWA	0.2 mg/m ³ TWA 2.5 mg/m ³ TWA	10 mg/m ³ TWAEV	10 mg/m ³ TWA
Methanol	200 ppm TWA 262 mg/m ³ TWA	200 ppm TWA	200 ppm TWA	200 ppm TWA 262 mg/m ³ TWA	200 ppm TWA	200 ppm TWA	200 ppm TWA	200 ppm TWA	200 ppm TWAEV 262 mg/m ³ TWAEV	200 ppm TWA
Ethyl benzene	100 ppm TWA 434 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	100 ppm TWA 434 mg/m ³ TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWA	20 ppm TWAEV	100 ppm TWA

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	Aerosol
Color	Orange
Odor	Aromatic
Odor threshold	Not available
pH	Not available
Melting point/range °C	Not available
Melting point/range °F	Not available

Boiling point/range °C	-44 °C
Boiling point/range °F	-47 °F
Flash point °C	-19
Flash point °F	-2
Flash point method used	Not available
Evaporation rate	Not available
Flammability (Solid, Gas)	Extremely flammable
Lower explosion limit	1.5 %
Upper explosion limit	10.9 %
Vapor pressure	Not available
Vapor density	Not available
Relative density	0.77-0.85
Solubility	Not available
Partition coefficient (n-octanol/water)	Not available
Autoignition temperature °C	Product is not self-igniting
Autoignition temperature °F	Product is not self-igniting
Decomposition temperature °C	Not available
Decomposition temperature °F	Not available
Viscosity	Not available

10. STABILITY AND REACTIVITY

Reactivity	Stable at normal temperatures.
Chemical stability	Not fully evaluated. In use, may form flammable/explosive vapour-air mixture.
Possibility of hazardous reactions	None known.
Conditions to avoid	Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing conditions.
Incompatible materials	No further relevant information available.
Hazardous decomposition products	None known.

11. TOXICOLOGICAL INFORMATION

Information on likely routes	Eyes.
-------------------------------------	-------

of exposure

Symptoms Eye irritation.

Delayed and immediate effects as well as chronic effects from short and long-term exposure No sensitizing effects known. No skin irritant effect. Causes eye irritation.

Numerical measures of toxicity

Chemical name	Inhalation LC50:	Dermal LD50:	Oral LD50:
Acetone	50100 mg/m ³ Rat	= 5800 mg/kg Rat >15700 mg/kg Rabbit	5800 mg/kg (Rat)
Propane	658 mg/L (Rat) 4h	-	-
n-Butyl acetate	0.74 mg/L Rat	= 10768 mg/kg Rat >17600 mg/kg Rabbit	10768 mg/kg Rat > 17600 mg/kg Rabbit
N-Butane	658 g/m ³ Rat	-	-
Isobutyl acetate	-	= 15400 mg/kg Rat >17400 mg/kg Rabbit	15400 mg/kg Rat > 17400 mg/kg Rabbit
Toluene	12.5 mg/L/4h (Rat)	8390 mg/kg (Rabbit)	636 mg/kg (Rat)
Ethylene glycol monopropyl ether	1530 ppm Rat	= 3089 mg/kg Rat 870 mg/kg Rabbit	3089 mg/kg Rat = 870 mg/kg Rabbit = 960 µL/kg Rabbit
Methylisobutyl ketone	2000 - 4000 ppm Rat	= 2080 mg/kg Rat 3000 mg/kg Rabbit	2080 mg/kg Rat = 3000 mg/kg Rabbit
Titanium dioxide	5.09 mg/L Rat	> 10000 mg/kg Rat	>10000 mg/kg Rat
Methanol	22500 ppm Rat	= 6200 mg/kg Rat 15840 mg/kg Rabbit	6200 mg/kg Rat = 15800 mg/kg Rabbit
Ethyl benzene	= 17.2 mg/L (Rat) 4 h	15354 mg/kg (Rabbit)	= 3500 mg/kg (Rat)

ATEmix (dermal) Not available

ATEmix (oral) Not available

ATEmix (inhalation-gas) Not available

ATEmix (inhalation-vapor) Not available

ATEmix (inhalation-dust/mist) Not available

Carcinogenicity

Chemical name	ACGIH OEL - Carcinogens	IARC	OSHA Carcinogens	NTP
Acetone	A4	-	-	-
Propane	-	-	-	-
n-Butyl acetate	-	-	-	-
N-Butane	-	-	-	-
Isobutyl acetate	-	-	-	-
Toluene	A4	Group 3	-	-
Ethylene glycol monopropyl ether	-	-	-	-
Methylisobutyl ketone	A3	Group 2B	Present	-
Titanium dioxide	A3	Group 2B	X	-
Methanol	-	-	-	-
Ethyl benzene	A3	Group 2B	X	-

**Canadian Province
carcinogenicity limits**

Chemical name	Alberta - Carcinogen	British Columbia - Carcinogen	Manitoba - Carcinogen	New Brunswick - Carcinogen	Nova Scotia - Carcinogen	Quebec - Carcinogen
Acetone	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
Propane	-	-	-	-	-	-
n-Butyl acetate	-	-	-	ACGIH A4	-	-
N-Butane	-	-	-	-	-	-
Isobutyl acetate	-	-	-	-	-	-
Toluene	-	-	ACGIH A4	ACGIH A4	ACGIH A4	-
Ethylene glycol monopropyl ether	-	-	-	-	-	-
Methylisobutyl ketone	-	IARC 2B	ACGIH A3	-	ACGIH A3	C3 Carcinogen
Titanium dioxide	-	IARC 2B	ACGIH A3	ACGIH A4	ACGIH A3	-
Methanol	-	-	-	-	-	-
Ethyl benzene	-	IARC 2B	ACGIH A3	-	ACGIH A3	C3 Carcinogen

12. ECOLOGICAL INFORMATION

Ecotoxicity

Hazardous for water, do not empty into drains.

Chemical name	Algae/aquatic plants	Fish LC50
Acetone	-	4.74 - 6.33mL/L Oncorhynchus mykiss 96h 6210 - 8120mg/L Pimephales promelas 96h = 8300mg/L Lepomis macrochirus 96h
Propane	-	-
n-Butyl acetate	=674.7mg/L Desmodemus subspicatus 72h	17 - 19mg/L Pimephales promelas 96h = 100mg/L Lepomis macrochirus 96h = 62mg/L Leuciscus idus 96h
N-Butane	-	-
Isobutyl acetate	-	101 - 123mg/L Leuciscus idus melanotus 48h = 101mg/L Leuciscus idus melanotus 48h = 17mg/L Oryzias latipes 96h
Toluene	=12.5mg/L Pseudokirchneriella subcapitata 72h >433mg/L Pseudokirchneriella subcapitata 96h	11.0 - 15.0mg/L Lepomis macrochirus 96h 14.1 - 17.16mg/L Oncorhynchus mykiss 96h 15.22 - 19.05mg/L Pimephales promelas 96h 5.89 - 7.81mg/L Oncorhynchus mykiss 96h 50.87 - 70.34mg/L Poecilia reticulata 96h = 12.6mg/L Pimephales promelas 96h = 28.2mg/L Poecilia reticulata 96h = 5.8mg/L Oncorhynchus mykiss 96h = 54mg/L Oryzias latipes 96h
Ethylene glycol monopropyl ether	-	> 5000mg/L Pimephales promelas 96h
Methylisobutyl ketone	=400mg/L Pseudokirchneriella subcapitata 96h	496 - 514mg/L Pimephales promelas 96h
Titanium dioxide	-	-
Methanol	-	13500 - 17600mg/L Lepomis macrochirus 96h 18 - 20mL/L Oncorhynchus mykiss 96h 19500 - 20700mg/L Oncorhynchus mykiss 96h = 28200mg/L Pimephales promelas 96h > 100mg/L Pimephales promelas 96h
Ethyl benzene	=4.6mg/L Pseudokirchneriella subcapitata 72h >438mg/L Pseudokirchneriella subcapitata 96h 2.6 - 11.3mg/L Pseudokirchneriella subcapitata 72h 1.7 - 7.6mg/L Pseudokirchneriella subcapitata 96h	11.0 - 18.0mg/L Oncorhynchus mykiss 96h 7.55 - 11mg/L Pimephales promelas 96h 9.1 - 15.6mg/L Pimephales promelas 96h = 32mg/L Lepomis macrochirus 96h

Chemical name	Algae/aquatic plants	Fish LC50
	=11mg/L Pseudokirchneriella subcapitata 72h	= 4.2mg/L Oncorhynchus mykiss 96h = 9.6mg/L Poecilia reticulata 96h

Persistence and degradability The product is degradable after prolonged exposure to natural weathering processes.

Bioaccumulation

Chemical name	CAS-No	Partition coefficient (log Kow)	Bioconcentration factor (BCF)
Acetone 67-64-1	67-64-1	-0.24	0.69 dimensionless species: fish
Propane 74-98-6	74-98-6	2.3 <=2.8	-
n-Butyl acetate 123-86-4	123-86-4	1.81 at 23 °C (ECHA_API); 2.3 at 25 °C (at pH 7, ECHA_API)	-
N-Butane 106-97-8	106-97-8	2.31 at 20 °C (at pH 7, ECHA_API) <=2.8	-
Isobutyl acetate 110-19-0	110-19-0	2.3 at 25 °C [OECD Guideline 117] (at pH 7, ECHA_API)	no significant bioconcentration
Toluene 108-88-3	108-88-3	2.73 at 20 °C (at pH 7, ECHA_API) 3.44 at 25 °C (at pH 7, ECHA_API); 3.93 at 20 °C (at pH 7, ECHA_API)	-
Ethylene glycol monopropyl ether 2807-30-9	2807-30-9	0.673 at 40 °C [Directive 84/449/EEC, A.8] (at pH 7, ECHA_API)	-
Methylisobutyl ketone 108-10-1	108-10-1	1.9 [OECD Guideline 117] (at pH 6.7, ECHA_API)	-
Titanium dioxide 13463-67-7	13463-67-7	-	-
Methanol 67-56-1	67-56-1	-0.77 (ECHA_API)	<10 dimensionless species: fish
Ethyl benzene 100-41-4	100-41-4	3.6 at 20 °C [Directive 84/449/EEC, A.8] (at pH 7.84, ECHA_API)	15 dimensionless species: fish

Mobility in soil Not available.

Other adverse effects Not available

13. DISPOSAL CONSIDERATIONS

Disposal information Dispose of in accordance with federal, state and local regulations. Do not puncture, incinerate, or crush. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches.

Contaminated packaging Completely empty cans should be recycled.

14. TRANSPORTATION INFORMATION

Shipping Descriptions

DOT ID-No UN1950

Proper shipping name Aerosols, flammable
Hazard Class(es) 2.1
Special Provisions LTD QTY

TDG

ID-No UN1950
Proper shipping name Aerosols, flammable
Hazard Class(es) 2.1
Special Provisions LTD QTY

IATA

ID-No UN1950
Proper shipping name Aerosols, flammable
Hazard Class(es) 2.1
Special Provisions LTD QTY

IMDG/IMO

ID-No UN1950
Proper shipping name Aerosols
Hazard Class(es) 2.1
Special Provisions LTD QTY

Marine Pollutants

Chemical name	CAS-No	USDOT Marine Pollutant	Canada TDG Marine Pollutant	IMDG Marine Pollutant
Acetone	67-64-1	-	-	-
Propane	74-98-6	-	-	-
n-Butyl acetate	123-86-4	-	-	-
N-Butane	106-97-8	-	-	-
Isobutyl acetate	110-19-0	-	-	-
Toluene	108-88-3	-	-	-
Ethylene glycol monopropyl ether	2807-30-9	-	-	-
Methylisobutyl ketone	108-10-1	-	-	-
Titanium dioxide	13463-67-7	-	-	-
Methanol	67-56-1	-	-	-
Ethyl benzene	100-41-4	-	-	-

Special Precautions

Multi-modal shipping descriptions are provided for informational purposes and do not consider container size. The presence of a shipping description for a particular mode of transport (sea, air, etc.), does not indicate that the product is packaged suitably for that mode of transport. All packaging must be reviewed for suitability prior to shipment, and compliance with the applicable regulations is the sole responsibility of the person offering the product for transport. People loading and unloading dangerous goods must be trained on all of the risks deriving from the substances and on all actions in case of emergency situations.

15. REGULATORY INFORMATION

State regulations

U.S. state Right-to-Know regulations

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Acetone	67-64-1	X	X	X
Propane	74-98-6	X	X	X
n-Butyl acetate	123-86-4	X	X	X
N-Butane	106-97-8	X	X	X

Chemical name	CAS-No	Massachusetts - RTK	New Jersey - RTK	Pennsylvania - RTK
Isobutyl acetate	110-19-0	X	X	X
Toluene	108-88-3	X	X	X
Ethylene glycol monopropyl ether	2807-30-9	-	X	X
Methylisobutyl ketone	108-10-1	X	X	X
Titanium dioxide	13463-67-7	X	X	X
Methanol	67-56-1	X	X	X
Ethyl benzene	100-41-4	X	X	X

California Prop. 65

Chemical name	CAS-No	California Prop. 65
Acetone	67-64-1	-
Propane	74-98-6	-
n-Butyl acetate	123-86-4	-
N-Butane	106-97-8	-
Isobutyl acetate	110-19-0	-
Toluene	108-88-3	Developmental
Ethylene glycol monopropyl ether	2807-30-9	-
Methylisobutyl ketone	108-10-1	Carcinogen Developmental
Titanium dioxide	13463-67-7	Carcinogen
Methanol	67-56-1	Developmental
Ethyl benzene	100-41-4	Carcinogen

U.S. Federal Regulations

**Consumer Product Safety
Commission**

This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.

US EPA SARA 313

Chemical name	CAS-No	CERCLA/SARA Hazardous Substances RQ	SARA 313 - Threshold Values
Acetone	67-64-1	5000 lb 2270 kg	-
Propane	74-98-6	-	-
n-Butyl acetate	123-86-4	5000 lb 2270 kg	-
N-Butane	106-97-8	-	-
Isobutyl acetate	110-19-0	5000 lb 2270 kg	-
Toluene	108-88-3	1000 lb 454 kg 1 lb 0.454 kg	1.0 %
Ethylene glycol monopropyl ether	2807-30-9	-	1.0 %
Methylisobutyl ketone	108-10-1	5000 lb 2270 kg	0.1 %
Titanium dioxide	13463-67-7	-	-
Methanol	67-56-1	5000 lb 2270 kg	1.0 %
Ethyl benzene	100-41-4	1000 lb 454 kg	0.1 %

US EPA SARA 311/312 hazardous categorization Not available

TSCA and Canadian Inventories

Chemical name	Inventory - United States - Section 8(b) Inventory (TSCA)	U.S. - TSCA (Toxic Substances Control Act) - Section 12(b) - Export Notification	DSL	NDSL
Acetone	X	-	X	-
Propane	X	-	X	-
n-Butyl acetate	X	-	X	-
N-Butane	X	-	X	X
Isobutyl acetate	X	-	X	-
Toluene	X	-	X	-
Ethylene glycol monopropyl ether	X	-	X	-
Methylisobutyl ketone	X	-	X	-
Titanium dioxide	X	-	X	-
Methanol	X	-	X	X
Ethyl benzene	X	-	X	-

Legend X - Listed

16. OTHER INFORMATION

NFPA

Health Not available
 Flammability Not available
 Instability Not available

HMIS

Health Not available
 Flammability Not available
 Physical hazards Not available

Notice: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on SDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by Regulatory Affairs

Issue date 05-Jun-2018

Revision date 07-Nov-2022

Revision note

Key to abbreviations

- ACGIH (American Conference of Governmental Industrial Hygienists)
- ATE (Average Toxicity Estimate)
- DSL/NDL (Domestic Substance List/Non-Domestic Substance List)
- HMIS (Hazardous Materials Identification System)

IARC (International Agency for Research on Cancer)
IATA (International Air Transport Association)
IMDG/IMO (International Maritime Dangerous Goods/International Maritime Organization)
NFPA (National Fire Protection Association)
NTP (National Toxicology Program)
OEL (Occupational Exposure Level)
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
PEL (Permissible Exposure Limit)
TSCA (Toxic Substance Control Act)
USEPA (United States Environmental Protection Agency)

Disclaimer

The information accumulated herein is believed to be accurate, but is not warranted to be, whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

End of Safety Data Sheet