




ELECTRONIC CONTACT CLEANER

EL™ 2204



For use on Electrical Equipment



Dielectric strength value: 26,800 Volts




Evaporation Rate: Very Fast



Non-flammable



Will not harm plastic



KB Solvency Strength (higher value, stronger the solvent): 31



HMIS Hazard Rating:
Health (2) • Flammability (0) • Reactivity (0)

- Non-conductive, non-flammable
- Safe on metal and many plastics
- Leaves no residue
- Equipped with an extension tube for hard-to-reach areas




PRESERVE. PROTECT. PREVENT.™

Sprayon® EL™ 2204 Electronic Contact Cleaner cleans sensitive equipment and precision instruments quickly without temperature control problems. Instant evaporation eliminates trapping of airborne contaminants and allows parts to be handled immediately. Packaged with extension tube for hard to reach areas. Because it is non-conductive, equipment can be cleaned while operating.

ELECTRICAL & ELECTRONIC

USES

- Printed circuits
- Relays & switches
- Radar equipment
- X-ray equipment
- Coin counters & Chutes
- Precision instruments
- Watches & clocks
- Office machines
- Timing devices • Meters
- Hydraulic & missile fuel systems
- Satellite communication equipment • Cameras
- Electronic games-TV-Video
- Telephone switch gears
- Computer systems & memory devices



EL2204

APPLICATION

Product should be sprayed in a well ventilated area. Shake well before using. Sprays best at room temperature (70°F). Hold can in upright position for best spray pattern. Use extension tube for pinpoint application.

PERFORMANCE

- EVAPORATION RATE: Very Fast
KB VALUE (Cleaning Power): 31
DIELECTRIC STRENGTH: 26,800 volts
PLASTIC SAFE: Yes
- NSF Registration Number 141750; K2 Rated.
 - No Class I Compounds
 - Non-flammable
 - Leaves no residue

PACKAGING

Stock #: S02204000
UPC Code: 0-75577-00315-0
Fill Wt: 10 oz.
Per Case: 12
Carton Dimensions:
L 10-7/8" x W 8-3/16" x H 8"

SHIPPING

Refer to section 14 of the material safety data sheet for proper transport information and labeling.

PROPERTIES

APPEARANCE: Colorless Volatile Liquid
ODOR: Mild Solvent
PROPELLANT: 134a - Tetrafluoroethane
WT/GAL: 11.33 g/l
SPECIFIC GRAVITY: 1.36
HAPS: None
Prop 65: No
% VOC: 0
VOC Compliant for CA & OTC states: Yes
FLASH POINT: None
FLAMMABLE: No
HAZARD RATING: 2, 0, 0

RESOURCES

MSDS/EDS/PRODUCT DATA SHEETS: Sprayon.com
CUSTOMER SERVICE: 1-800-777-2966
TECHNICAL INFORMATION: 1-800-251-2486



© 2010 Sprayon® Products Made in U.S.A.

Distributed by:

Lawson Products, Inc.

To order these and other products, contact us:
866-529-7664 lawsonproducts.com

PRESERVE. PROTECT. PREVENT.



Sprayon® Products
101 Prospect Ave. NW
Cleveland, OH 44115
Sprayon.com
1-800-777-2966

310-PDS-EL2204